



ALDERLY RANGE




powered by
TRIDONIC

60 degree



90 degree



IP20
 IK02
 LB
 L70/B50
50,000 hrs

The Alderley LED downlighter is equipped with the state-of-the-art LED technology, making it an ideal choice for a wide range of commercial applications, boasting an efficacy of up to 111 lumens per watt.

The downlighter is available in three sizes and two colour temperatures, and comes with the option of a 60-degree or 90-degree reflector, making it suitable for various applications such as corridors and open plan areas.

The Alderly range seamlessly integrates with SCC's standard options, offering choices such as dimmable functionality and emergency configurations. Additionally, these luminaires can be seamlessly integrated into our intelligent lighting systems through wireless options, ushering in a new era of versatile illumination solutions.

Part code	Power W	Output lm	Diameter mm	Height mm	Cut out mm	CCT K	Weight kg
LUXALD/1/1000/3K	10	1060	120	64	100	3000	0.5
LUXALD/1/1000/4K	10	1110	120	64	100	4000	0.5
LUXALD/2/1000/3K	10	1100	170	93	145	3000	0.8
LUXALD/2/1000/4K	10	1120	170	93	145	4000	0.8
LUXALD/2/2000/3K	20	2130	170	93	145	3000	0.8
LUXALD/2/2000/4K	20	2210	170	93	145	4000	0.8
LUXALD/3/2000/3K	20	2200	225	113	210	3000	1.2
LUXALD/3/2000/4K	20	2250	225	113	210	4000	1.2
LUXALD/3/3000/3K	30	3070	225	113	210	3000	1.2
LUXALD/3/3000/4K	30	3180	225	113	210	4000	1.2

DD = DALI Dimmable
 E = Emergency
 60 = 60deg reflector

SD = SwitchDim
 ST = Self Test Emergency
 90 = 90deg reflector

MD = Mymesh Dim
 ME = Mymesh Emergency
 TW = Tunable White

CD = Casambi Dim
 SL** = Slave