



EVERSLEY RANGE



powered by
TRIDONIC



IP65
 IK10
 L80/B10
72,000 hrs

The Eversley range incorporates impact resistant aluminium cast base and polycarbonate diffuser along with Tridonic high-performance LED board and driver making the bulkhead a highly efficient lighting fixture that can meet even the most rigorous energy-saving requirements. It is ideal for commercial and domestic use and has been designed to be both economical and efficient.

Supplied as CRI 80 as standard, with a high colour stability of 3 MacAdam steps, the Eversley is available with white or black base and either cool or warm white colour temperature and along with a range of control options including corridor function. The emergency range of the Eversley emergency versions are fitted with the latest lithium iron phosphate LiFePO4 battery technology, which has a 3-year battery warranty.

The Eversley range seamlessly integrates with SCC's standard options, offering choices such as dimmable functionality and emergency configurations. Additionally, these luminaires can be seamlessly integrated into our intelligent lighting systems through wireless options, ushering in a new era of versatile illumination solutions.

Part code	Power W	Output lm	Length/Width mm	Height mm	Efficacy lm/W	CRI	CCT K
LUXEVER/1500/3K	13	1519	276	97	114	80	3,000
LUXEVER/1500/4K	13	1599	276	97	120	80	4,000
LUXEVER/2000/3K	17	1995	276	97	114	80	3,000
LUXEVER/2000/4K	17	2100	276	97	120	80	4,000
LUXEVER/2500/3K	21	2447	276	97	114	80	3,000
LUXEVER/2500/4K	21	2574	276	97	120	80	4,000

DD = DALI Dimmable
E = Emergency
CF = Corridor Function

SD = SwitchDim
ST = Self Test Emergency
MW = Sensor On/Off

MD = Mymesh Dim
ME = Mymesh Emergency
WH = White base

CD = Casambi Dim
SL** = Slave
BL = Black base